

560556

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 December 2004 (29.12.2004)

PCT

(10) International Publication Number
WO 2004/113906 A1

(51) International Patent Classification⁷: **G01N 29/24**

(21) International Application Number:
PCT/GB2004/002648

(22) International Filing Date: **18 June 2004 (18.06.2004)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
0314357.5 19 June 2003 (19.06.2003) GB

(71) Applicant (for all designated States except US): **PII LTD**
[GB/GB]; Atley Way, Cramlington, Northumberland, Tyne
and Wear NE23 1WW (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **PAIGE, David**
[GB/GB]; 23 Wilmington Close, Kenton Bank Foot,
Newcastle upon Tyne, Tyne and Wear NE3 2SF (GB).
MERCEL, Robert, Andrew [GB/GB]; 11 Falstone Cres-
cent, Ashington, Northumberland, Tyne and Wear NE63
0TY (GB). **SOWERBY, Ian** [GB/GB]; 8 Kingsway, North
Shields, Northumberland, Tyne and Wear NE30 2LY (GB).


(74) Agents: **CALDERBANK, Roger et al.**; Mewburn Ellis
LLP, York House, 23 Kingsway, London Greater London
WC2B 6HP (GB).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: **ELECTROMAGNETIC ACOUSTIC TRANSDUCER**



(57) Abstract: An electromagnetic acoustic transducer (12, 24) has one or a plurality of magnets for applying a DEC magnetic field to a material (4, 25) under test, and an electrical coil (2, 23) supplied by an alternating current source for providing an AC magnetic flux within the material under test. A wear plate (16, 26) engages with an slides along the surface of the material under test. The wear plate (16, 26) is of electrically conductive ferromagnetic material and has apertures (17, 31) therein. Thus, both the DC field and the ACT flux can penetrate the material under test and create ultrasonic vibration of that material.

WO 2004/113906 A1